

SELF-POWERED SCISSOR LIFT

Navigator 4.5

Designed for purpose. Built to last.

4.5 m

WORKING HEIGHT

150 kg

SAFE WORKING LOAD

360 kg

MACHINE WEIGHT



SELF-POWERED ELEVATION

OVERVIEW

A self-powered, push-around scissor lift. Step in, release the brakes, turn the handle and elevate to your chosen working height, with materials and tools onboard. Power-free working, 24/7. The narrowest push-around on the market.

KEY FEATURES

- Lightweight
- Easy to manoeuvre
- Failsafe Systems
- Lifts both operative and tools to height
- 630mm wide and fits through a door frame
- Minimum repair cost
- Carbon Zero
- Patent Granted
- 97% Recyclable Product

APPLICATIONS

Clean Rooms & Pharmaceuticals

Schools & Universities

Manufacturing

Data Centres

Retail Stores

sales@navigatorlifts.com

+44 333 200 8691

navigatorlifts.com

TECHNICAL SPECIFICATIONS

The details.

WORKING DIMENSIONS

Working Height	4.5m
Platform height	2.5m
Working Footprint	1.1m (L) x 0.63m (W)
Platform Dimensions	0.98m (L) x 0.63m (W)
Safe Working Load	150kg
Maximum Side Force	200N
Maximum windspeed outdoors (with stabilisers)	12.5 m/s
Maximum Gradient	1 Degree
Max Load Per Fixed Wheel	880kg
Max Load per Swivel Castor	880kg
Machine Weight	360kg

CLOSED DIMENSIONS

Length	1.1m
Width	0.63m
Height	1.79m

PERFORMANCE

Ascent / descent rotations: 30

SAFETY FEATURES

- Anti-Climb Vertical Guardrail
- Tethering Accessories for Tools
- Anti-Surf Brakes
- Ratchet wind up handle for immediate stop
- Transport and Deck Lock
- Winch Point
- Optional Catcher Accessory
- Optional Outriggers Accessory for Outdoor Use



Certified to BS EN 280-1. Indoor and outdoor rated when fitted with optional outdoor stabilisers.

Specifications, descriptions and illustrative material are accurate at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories not included in the standard specification.

Technical content: supplied 2025 data sheet | Brand layout: October 2026